



BETON: B30
 WŁOŚCIWYŚĆ BETONU: W8.
 STAL ZBROJENIOWA: A40-S10S
 A11-34GS
 KLASA ŚRODOWISK: 2a (wg PN-B-03264-1999)
 OTULINA: min $a = 20$ mm.

UWAGA: W MIEJSCU OTWORÓW PRĘTY PRZECIĄĆ I WGIAĆ W ŚCIANĘ.

WYKAZ STALI ZROBIOJENIOWI		DLUGOŚĆ ŁĄCZNA	
NR	GAŁ. STALI	AO-Siód	AO-Siód
Stoż405	Deucosio	12	18
1	m 18	5,20	3,90
2	ø 18	6,20	16,2
3	ø 18	5,32	4,0
4	ø 18	5,67	4,0
5	ø 18	5,50	6,0
6	ø 18	7,00	4,0
7	ø 18	5,10	4,0
8	ø 18	5,54	5,2
10	ø 18	11,2	4,6
11	ø 18	10,86	4,4
12	ø 18	4,00	8,8
13	ø 12	5,10	4,4
14	ø 12	2,90	7,4
15	ø 12	4,00	6,4
16	ø 12	5,00	6,4
17	ø 12	5,90	3,0
18	ø 12	5,10	10,4
19	ø 12	4,76	4,2
20	ø 12	6,35	2,8
21	ø 12	2,00	2,5=10
22	ø 8	0,92 x11=22	20,24
23	ø 8	1,12	9
24	ø 8	1,12	9
RAZEM		mb.	30,32
MASA POZOST. ø	kg	12,0	12,0
MASA STALU GAŁ. STALI	kg	12,0	12,0
MASA STALI OGÓŁEM	kg	24,34	24,34
		m	12
		ø 12	18
		18,35,56886,92	16,50,01919,41
		21,422,1	

[illegible]